Street name sign blank for speed limit of 30 MPH and greater

Series "D" Lettering

See Detail 2054-2A

Detail "A"
Street name sign bracket
to square tube post
(MCDOT Detail 2062-5)

Detail "B"
Sign to sign bracket
(MCDOT Detail 2062-6)

NOTES

1. Sign lengths shall be determined by the number of letters and spacing requirements.
2. All signs shall be fabricated with 6 inch white upper-case and lower-case letters.
3. Diamond Grade (Type IX or Type XI) sheeting shall be used for all letters and background.
4. Background color shall be:
   Blue - private roadways
   Green - open and declared public roads
5. All signs shall be mounted on a 2.6 LB/FT square perforated sign post.
6. Thickness of all sign blanks shall be 0.125 inches.
7. Square tubing shall be assembled as shown in MCDOT Standard Detail 2058.
8. Signs shall be installed per standard location shown below left.
9. All dimensions are in inches, except as noted.
10. Refer to MCDOT Standard Detail 2061-10B for sign blanks.
11. Use Grade #2, Zinc coated, 18 NC thread, 3" x 5/16" bolt with flat washer under nut and flat washer under head to attach sign to bracket.

Height to bottom of sign

Standard location of
street name signs

Square Tube Post
(2.6 LB./FT)

(1) As measured from top of sidewalk, top of curb, top of pavement or ground (whichever is higher)

Sign post installation

(Not to scale)

REVISED DATE	12/2016

MARICOPA COUNTY DEPARTMENT OF TRANSPORTATION	STREET NAME SIGN INSTALLATION DETAILS POSTED SPEED LIMIT OF 30 MPH OR GREATER	DATE:	DETAIL NO.
STANDARD DETAIL		06/2002	2054-2