COVER ASSEMBLY

DETAIL B
(BOLT DOWN)

SECTION C-C
(TYPICAL)

SECTION A-A

SECTION D-D
(LIFT HANDLE)

SECTION E-E
(LIFT HANDLE)

NOTES:

1. PULL BOX COVER SHALL BE 1/4-INCH DIAMOND PLATE GALVANIZED OR MILD STEEL AND SHALL PROVIDE A SKID RESISTANT SURFACE.
2. PULL BOX COVER SHALL BE SECURED TO PULL BOX USING A SPRING NUT ASSEMBLY.
3. PULL BOX COVERS SHALL HAVE THE WORDS 'MCDOT ATMS' IN 1-INCH HIGH LETTERS.
4. COVER PULL SLOTS SHALL BE A MINIMUM OF 7-1/2 -INCH WIDE AND BE EQUIPPED WITH LIFT HANDLES.
5. COVER SLOTS AND LIFT HANDLES SHALL BE RATED FOR A MINIMUM OF 3,000 LBS PULLING FORCE.

MARICOPA COUNTY DEPARTMENT OF TRANSPORTATION STANDARD DETAIL	ITS FIBER OPTIC TYPE E PULL BOX COVER ASSEMBLY	DATE: 10/25/2013	DETAIL NO. 4806-2