SECTION A-A

NOTES:

1. CONCRETE SHALL BE CLASS 'B' PER SECTION 725.
2. CONSTRUCTION SHALL CONFORM TO SECTION 340.
3. SIDEWALK SURFACE TO MATCH 1½% SLOPE FROM TOP OF CURB.
4. A SPECIAL DESIGN IS REQUIRED WHEN THE GUTTER GRADE AROUND THE RETURN EXCEEDS 2%.
5. THIS DETAIL TO BE USED FOR INTERSECTIONS OF RESIDENTIAL-RESIDENTIAL AND RESIDENTIAL-MINOR COLLECTOR ROADWAYS.

CURB HEIGHT	RETURN RADIUS (**R**) @ FACE CURB	MINIMUM WING LENGTH (**W**) ALONG FACE OF CURB	℄ OFFSET (**D**) @ FACE OF CURB	CURB RAMP MINIMUM LENGTH (**L**)
4"	20' or 25'	4'-6"	10"	5'-0"
6"	25'	6'-6"	6"	7'-6"

MARICOPA COUNTY DEPARTMENT OF TRANSPORTATION	RADIAL CURB RAMPS FOR RESIDENTIAL INTERSECTIONS	DATE:	DETAIL NO.
STANDARD DETAIL		11/03/2016	2032